

Technical Data Sheet Nawkaw Li-THX

Lithium-Thick Stain for Masonry and Concrete

Nawkaw

Changing the color of masonry

Official US supplier of Reckli formliners



DESCRIPTION

Nawkaw Li-THX is the thicker version of our NEW lithium stain for concrete and masonry surfaces. It penetrates and bonds to any concrete or masonry surface yielding a paint-like appearance. Li-THX is ideal for hiding slight surface details and imperfections.



COVERAGE / TREATMENT YIELD

200-400 sq ft per gallon depending on the absorbency of the substrate

PHYSICAL PROPERTIES

- Form viscous liquid, color matches label
- Total Solids 36-40 % Specific Gravity: 1.15 – 1.17
- pH 11
- Film yes
- Flash Point: None
- 20% Recycled Glass Content
- V.O.C. Content 0 g/L
- Freeze point 32° F (0° C)
- Abrasion Resistance excellent
- Depth of Surface Penetration 2-8mm (non pigment chemistry)
- Shelf Life 6 months in factory sealed container

APPLICATION

- Coverage rate varies with concrete quality and finish

RECOMMENDED FOR

- Brick
- Concrete
- Concrete Block
- Precast
- Tilt-up

DRYING TIME

1-2 hours